

Energy Storage EV Charger

208kwh/120kw DC Charger

☺ Product Features

Constant power output between 200~1000V, Energy storage capacity 208kwh

With breathing indicator for standby, charging and various common fault states

support online operation and management, real-time monitoring of equipment

10-inch touch screen display and 24 inch advertisement screen (optional)

Support online operation and management, real-time monitoring of equipment status, customised tariff table (OCPP 1.6J communication).

OTA upgrade, dialog and troubleshooting

∞ Main function

QR-code/BLE/Card/Plug and Charge

10 inch touch screen display (EN)

24 inch advertisement screen display (Optional)

BLE + Eth/Wi-Fi/4G (Optional)

Ethernet RJ-45/4G

OCPP 1.6J

IP 54



Main Performance And Characteristics

Parameters	Model	T208-120
Input	Power Supply	3P+N+PE
	Voltage	400VAC±20%
	Max CURRENT	167A
	Frequency	50/60Hz±10%
Output	Voltage	CCS2: 200 ~ 1000VDC
	Max Current	250A
	Rated Power	120kw
	Energy Storage	208kwh
User Interface	Charge Plug	CCS2
	Cable Length	6 Meters (Optional)
	Enclosure	Galvanised Steel
	LED Indicator	Green/Yellow/Blue/Red
	LCD Display	10 Inch Touchscreen (And Advertisement Screen Optional)
	RFID Card Reader	Yes
	POS Terminal	Optional
Communication	Start Method	QR-Code/Plug And Charge
	Communication Protocol	Ethernet/4G (Optional) OCPP 1.6J/OCPP2.0J (Optional)
Electrical Performance	Efficiency	≥96% (Half Load And Above)
	Power Factor	≥0.99(Rated Load)
	Harmonic Distortion Rate	≥5%(Half Load And Above)
	Ripple Coefficient	≤1%(Peak To Peak)
Safety	Energy Meter	MID (PTB Optional)
	Emergency Stop	Yes
	RCD	Type A
	Protection Grade	IP54
	Electrical Protection	Over-Current, Leakage, Short Circuit, Grounding, Lightning, Under-Voltage, Over-Voltage And Over-Temperature
	Certification	CE, RCM
	Standard	EN/IEC 61851-1, EN/IEC 61851-23, IEC 61851-24, EN/IEC 61851-21-1
Workig Environment	Installation	Floor Mounted
	Cooling	Liquid Cooling
	Noise	65dB
	Temperaturerange	Working At -10~+60°C
	Working Humidity	95% (Non-Condensation)
	Altitude	≤2000m
Package	Product Size	1190*1350*2120mm(W*D*H)
	N.W.	2.6T
Others	Packaging Material	Wooden Box
	Warranty	2 Years